

COLORSIVIT MONO

Transparent varnish for porous substrates

Description

1 Component product easy to be applied based on waterborne aliphatic polyurethane dispersion.

Uses

Water repellent treatment for:

- Stone floors
- Concrete
- Porous substrates

Preparation of the substrate

- When the substrate is brand new, it is advisable to wait for the seasoned time.
- The substrate must be clean, and not polluted by oils, dust or any material not properly stuck .
- 1 Component product easy to be applied based on waterborne aliphatic polyurethane dispersion.



Application

COLORSIVIT MONO can be applied alone or diluted with water in different proportion, depending on the final purpose.

Mix the product and apply it by roll, brush or low pressure spray.

Technical Data

Colour	Transparent, colourless	
Density	1,00-1,05 g/ml	
Solid content	32%	
Tack free time	at 35°C and 50% U.R.	4-15 minutes
	at 25°C and 50% U.R.	20-30 minutes
	at 7°C and 50% U.R.	35-45 minutes
Consumption	1,0 lt for 5-10 sqm	
Flash point	Non applicable	
Overcoat time	at 25°C and 50% U.R. min 2 hours – max 36 hours	
Application conditions	Temperatures between 7°C and 35°C and U.R. < 80%	
Solvent to clean the tools	Water	
Dangerous symbols on labels	None	
Storage	12 months. Keep it in a dry place at a temperature between 5°C and 35°C	